

**Description**

Ultra clear, top-coated polyester film with glossy surface and excellent dimensional stability

**Release film**

Polyester film, siliconised on one side, 36 micron

**Adhesive**

Solvent polyacrylate, removable

**Area of use**

Ultra clear, colourful advertising efforts and glass decorations for indoor and short-term outdoor application on windows. Dry and wet applications are possible.

**Printing method**

Inkjet printing with solvent based inks, UV- or Latex inks

**Technical Data**

<b>Thickness*</b> (without protective paper and adhesive)	70 micron
<b>Dimensional stability</b> (FINAT TM 14)	adhered to steel shrinkage 0.1 mm max.
<b>Temperature resistance***</b>	adhered to aluminium, -30°C to +70°C, no variation
<b>Adhesive power*</b> (FINAT TM 1, after 24h, glass)	2 N/25 mm
<b>Tensile strength</b> (DIN EN ISO 527)	along: min. 70 MPa across: min. 130 MPa
<b>Elongation at break</b> (DIN EN ISO 527)	along: min. 110% across: min. 50%
<b>Shelf life**</b>	2 years
<b>Application temperature</b>	> +10°C
<b>Service life by specialist application</b> under vertical outdoor exposure (normal climate of Central Europe)	1 year (not printed)

\* average

\*\* in original packaging, at 20°C and 50% relative humidity

\*\*\* normal climate of Central Europe

**Note**

Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. The batch traceability according to ISO 9001 is possible on the basis of the roll number

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.

